



OUTDOOR METAL POWER SUPPLIES

KPS-V12-150W67-5Y-SM

 <p>IP 67 DUST AND WATER PROTECTED</p>	 <p>OVERHEAT PROTECTION</p>	 <p>5 YEAR EXTENDED WARRANTY</p>	 <p>OVER VOLTAGE PROTECTION</p>	 <p>SHORT CIRCUIT PROTECTION</p>	 <p>50 000 h LIFETIME 50 000 H</p>	 <p><0,3 % MINIMIZED DEFECTIVE RATE</p>
--	--	---	--	---	--	--



TECHNICAL INFORMATION

Output Voltage	12V	24V
Rated Current	12,5 A	6,25 A
Rated Power	150 W	150 W
Ripple & Noise (max.)	<100mVp-p	<100mVp-p
Setup, Rise Time	1500ms/230 VAC	1500ms/230 VAC

STORAGE AND OPERATING CONDITIONS

Working Temp.	-30°C ~ 50°C
Working Humidity	20°C ~ 95%RH
Storage Temp.	-40°C ~ 80°C
Storage Humidity	10°C ~ 95%RH

PACKAGING

Product Dimension	279x57x25 mm
Products Net Weight	680 g
PCS/Cartron (QTY)	25 PCS
Master Carton Size	415x330x180 mm
G. Weight/Cartron	18 kg

Input Voltage	Input Frequency	Efficiency (Typ.)	Input Current
170 - 250 V	50/60 Hz	87%	230 V : 1,45 A max.